


UNIVERSAL

PART#	O.E.M	APPLICATION
195-057	Universal	
<p>10" Plastic Wheel Measures: 10" OD X 1/2" ID Wheel hub is 1-1/2" offset. Thread style: Diamond (Will accept our 235-036 axle bolt). NOTE: For 10" wheel with rib tread, please see our 185-033.</p>		
185-033	Universal	
<p>10" Steel Wheel Measures: 10" OD X 1/2" ID Wheel hub is 2-1/16" offset. Thread style: Rib. Replaceable ball bearing type wheel for longer life.</p>		




ARIENS

215-095	54044 / 54055 05404400 05405500 Gilson# 1140 / 1044 Roper# 1554H / 1553H Simplicity# 154486 Troy Bilt# 1714	
<p>Roller Bearing & Race Measures: 3/4" ID X 1-25/32" OD X 21/32" HT (Bearing# LM11949 and LM11910)</p>		
215-103	54069 / 54070 05406900 05407000	
<p>Roller Bearing & Race Measures: 1" ID X 1.988" OD X .43" HT (Bearing# L44610 and L44643)</p>		
225-825	55112 05511200	
<p>Bushing Fits rear tine tiller 901011 20" Measures: 3/4" ID X 1" OD X 3/4" HT</p>		
370-302	129359 001292300 AYP# 4459J AYP# 6554J	
<p>Left Hand Tiller Tine Three 3/8" bolt holes, 2-5/8" or 3-1/8" centres. 3" wide cut, 12" bolo tine.</p>		
370-306	129259 001292200 AYP# 4460J AYP# 6554J	
<p>Right Hand Tiller Tine Three 3/8" bolt holes, 2-5/8" or 3-1/8" centres. 3" wide cut, 12" bolo tine.</p>		



AYP

PART#	O.E.M	APPLICATION
285-703	3066J 188532	
<p>Clutch Cable Fits on Tillers. Cable length: 44" X Conduit length: 41-1/2" X Spring length: 2-1/2".</p>		



GILSON

240-614	1054 Atlas# 74-15 General Power# 774-547 Lawn Boy# 700414 National# 471224 Simplicity# 118118	
<p>Oil Seal Fits on Tillers - 1/4" seal height. Size: 1" ID X 1-1/2" OD (double seal)</p>		
416-826	1060	
<p>Hitch Pin Measures: 1-3/4" L X 1/8" diameter #16 mfg. Number (Sold in multiples of 10)</p>		
418-509	11780 Lawn Boy# 700799	
<p>Tiller Tin Pin Measures: 1/2" diameter X 2" length (For other sizes - see our "ASSORTMENT" heading, under "Tiller Tine Pin Assortment") (Sold in multiples of 10)</p>		



HONDA

370-608	72461-723-700 72461-723-750 Code# 3471851	
<p>Left Hand Tiller Tine Fits left hand. Two 3/8" diameter mounting holes on 3-1/8" centre to centre, 14" bolo tine, 3" wide cut. Fits Honda tiller models: FR500, FR500K1, FR700 and FR700K1.</p>		
370-609	72465-723-700 Code# 3471869	
<p>Right Hand Tiller Tine Fits right hand. Two 3/8" diameter mounting holes on 3-1/8" centre to centre, 14" bolo tine, 3" wide cut. Fits Honda tiller models: FR500, FR500K1, FR700 and FR700K1.</p>		


HUSQVARNA

PART#	O.E.M	APPLICATION
370-608	532 1011-94	 <p>Left Hand Tiller Tine Fits left hand. Two 3/8" diameter mounting holes on 3-1/8" centre to centre, 14" bolo tine. Fits MTD tiller models: 099, 218-355-000, 218-385-000, 219-355-000, 219-385-000, Sears 247.298611 and 247.298712. Fits Husqvarna tiller models: CRT81 and CRT83.</p>
370-609	532 10 11-93	 <p>Right Hand Tiller Tine Fits right hand. Two 3/8" diameter mounting holes on 3-1/8" centre to centre, 14" bolo tine. Fits MTD tiller models: 099, 218-355-000, 218-385-000, 219-355-000, 219-385-000, Sears 247.298611 and 247.298712. Fits Husqvarna tiller models: CRT81 and CRT83.</p>


JOHN DEERE

370-302	M130045	 <p>Left Hand Tiller Tine Fits left hand. Three 3/8" dia. mounting holes, 2-5/8" or 3-1/8" centers. 3" wide cut, 12" bolo tines.</p>
370-306	M130044	 <p>Right Hand Tiller Tine Fits right hand. Three 3/8" dia. mounting holes, 2-5/8" or 3-1/8" centers. 3" wide cut, 12" bolo tines.</p>







MERRY TILLER

240-135	706-0344 National# 340356 Snapper# 1-3681	 <p>Oil Seal Fits most Tiller models. Measures: 1-1/4" ID X 1-11/16" OD X 7/32" HT</p>
----------------	---	--

MTD

875-999	754-0434 954-0434	 <p>Drive belt Fits Cub Cadet tillers, 2008 & newer. Fits MTD tillers, 2009 and newer. For MTD 430, 440 and 450 model series rear tine tiller 1997 and later. Size: 1/2" X 58-1/4" L. (Type 1).</p>
----------------	----------------------	---




MTD continued

PART#	O.E.M	APPLICATION
225-045	748-0110	 <p>Bronze Flange Bushing Fits MTD Tillers. Measures: 5/8" ID X 7/8" OD X 5/8" HT</p>
225-300	748-0855 Jacobsen# 545549 Toro/Wheel# 2119-127 Yardman# 065274	 <p>Bronze Flange Bushing Fits MTD Tiller model 766 and others applications. Measures: 5/8" ID X 3/4" OD X 1" HT</p>
418-749	714-0126 Snapper# 1-0211	 <p>Woodruff Key - # 9 Key (Sold in multiples of 10) Measures: 3/16" W X 3/4" L. (For more sizes see - "Assortments" heading under "Woodruff Key Assortment")</p>
418-798	714-0103 714-0135	 <p>Woodruff Key - Number 91 key (Sold in multiples of 10) Measures: 1/4" W X 3/4" L. (For more sizes see - "Assortments" heading under "Woodruff Key Assortment")</p>
240-804	921-04031	 <p>Oil Seal Fits axle seal on Horse / Troy Bilt / MTD model Tillers. Measures: 1" ID X 1-1/2" OD</p>
495-147	721-0179 921-0179 Cub Cadet# 721-0179 Cub Cadet# 921-0179 Troy Bilt# 721-0179 Troy Bilt# 921-0179	 <p>Oil Seal Fits on MTD Snowblowers. Fits MTD 600 series (1992 thru 1993) and 400, 500 & 600 series (1994 thru 2004). Measures: 3/4" ID X 1-1/8" OD X 1/8" HT.</p>

MTD continued

PART#	O.E.M	APPLICATION
370-302	742-0105 Noma# 600089 Roto Hoe# 1569	
<p>Left Hand Tiller Tine Fits Troy Bilt models: HORSE and PONY. Three 3/8" bolt holes, 2-5/8" or 3-1/8" centres. 3" wide cut, 12" bolo tine.</p>		
370-306	742-0106 Noma# 600090 Roto Hoe# 1570	
<p>Right Hand Tiller Tine Fits right hand. Three 3/8" bolt holes, 2-5/8" or 3-1/8" centres. 3" wide cut, 12" bolo tine.</p>		
370-608	742-0107	
<p>Left Hand Tiller Tine Fits left hand. Two 3/8" diameter mounting holes on 3-1/8" centre to centre, 14" bolo tine. Fits MTD tiller models: 099, 218-355-000, 218-385-000, 219-355-000, 219-385-000, Sears 247.298611 and 247.298712. Fits Husqvarna tiller models: CRT81 and CRT83.</p>		
370-609	742-0108	
<p>Right Hand Tiller Tine Fits right hand. Two 3/8" diameter mounting holes on 3-1/8" centre to centre, 14" bolo tine. Fits MTD tiller models: 099, 218-355-000, 218-385-000, 219-355-000, 219-385-000, Sears 247.298611 and 247.298712. Fits Husqvarna tiller models: CRT81 and CRT83.</p>		







TROY BILT

875-328	50134 / GW-50134	
<p>Kevlar V-Belt Fits models 20594-20597 Pony III tillers; 5 Hp Pony and 3.5 Hp Junior II models. Measures: 3/8" W X 28" L</p>		
875-685	1128-1 GW-1128-1	
<p>Drive belt Fits older Horse models. Fits 2-speed HORSE models, serial numbers 1001 to 314150. Measures: 1/2" W X 21-3/4" L (Can also use our Kevlar belt# 875-420 = 1/2" X 20")</p>		
875-686	9245 GW-9245	
<p>Drive belt Fits 4-speed HORSE models. Measures: 1/2" W X 22-1/4" L</p>		




TROY BILT continued

PART#	O.E.M	APPLICATION
875-278	9201 GW-9201 Garden Way# 1909404	
<p>Drive belt Fits models 20458-20463 Pony and 20558 Super Pony. For 5 Hp engines. Measures: 1/2" W X 23-3/4" L (Can also use our Kevlar belt# 875-424 = 1/2" X 24")</p>		
240-940	2111 88174	
<p>Drive Disc Tiller reversing drive disc. Used on newer Horse models DP630 thru 1260 since 1989. Measures: 3/8" ID X 3-3/4" OD</p>		
430-488	9243	
<p>Starter Key Fits Troy Bilt as well as John Deere, MTD, Toro / Wheel Horse and many others.</p>		
240-507	9618 Garden Way# GW9618 GW9618099	
<p>Oil Seal Fits tine seal on Horse model Tiller. Measures: 1-1/4" ID X 2" OD</p>		
240-804	9621 921-04031	
<p>Oil Seal Fits axle seal on Horse model Tiller. Measures: 1" ID X 1-1/2" OD</p>		
495-147	721-0179 921-0179	
<p>Oil Seal Fits on MTD Snowblowers. Fits MTD 600 series (1992 thru 1993) and 400, 500 and 600 series (1994 thru 2004). Measures: 3/4" ID X 1-1/8" OD X 1/8" HT.</p>		

TROY BILT continued

PART#	O.E.M	APPLICATION
285-105	2163	 <p>Four Speed Horse Spring Fits HORSE models serial# 1206800100101 - up. Measures: 3-3/8" overall length</p>
285-115	1492	 <p>Two Speed Horse Spring Fits Pony & Horse models serial# 1001-639999. Measures: 3-3/8" overall length</p>
370-092	1026A GW-1026A	 <p>Tine Shaft Fits rear tine Tillers models Horse 1, 2, 3 thru 6, 7 and 8 Hp. Models: OPC Horse and PTO Horse. Size: 7" Long X 1-1/4" Shaft OD, Tapers down to .735" OD on both ends, 1/2"-20 female threads on each end.</p>
215-015	11522 Woods# 2303	 <p>Tapered Roller Bearing Set Fits above tine shaft. For HORSE models. Measures: 1-1/4" ID X 2-21/64" OD X 21/32" HT (Bearing# LM67048 / LM67010)</p>
370-302	1270-1A John Deere# M130045 Noma# 600089 Roto Hoe#1569	 <p>Left Hand Tiller Tine Fits HORSE and PONY models. Three 3/8" bolt holes, 2-5/8" or 3-1/8" centres. 3" wide cut, 12" bolo tine.</p>
370-306	1270-2A John Deere# M130044 Noma# 600090 Roto Hoe#1570	 <p>Right Hand Tiller Tine Fits HORSE and PONY models. Three 3/8" bolt holes, 2-5/8" or 3-1/8" centres. 3" wide cut, 12" bolo tine.</p>

TILLER TINE SET

PART#	O.E.M	APPLICATION
370-310	1901118	<p>Tiller Tine Set 12" - For HORSE and PONY models. Also found on Ariens, AYP, John Deere, MTD, Noma / Canadiana and Roto Hoe tillers</p> <p>Kit contains the following: (8) 370-302 left hand tiller tines (8) 370-306 right hand tiller tines and (32) Cap screws, hex nuts and lock washers</p> 
370-298		<p>Also available by itself is a Hardware Kit for above When ordering part# 370-298 you will receive: (32) Cap Screws, (32) Hex Nuts, (32) Lock Washers.</p> 
370-320	GW-1901 / 742-04116 / 742-04117 742-04117-0637 / 742-041116-0637	 <p>Tiller Tine Set - 10" Used on Troy Bilt Bronco, Pro-line, Tuffy from 2005 > on. Kit contains the following: (8) left hand tiller tines; (8) right hand tiller tines and; (32) Cap screws, hex nuts and lock washers.</p>
<p>BANTA's TOLL FREE FAX ORDERING# 1-800-359-1993 (Canada only) or place your orders on-line @ www.bantasaw.com Email your inquiries to sales@bantasaw.com</p>		